

**FORCE  
INDUSTRIES  
DIVISION**

American Solder & Flux Co., Inc. • 28 Industrial Boulevard • Paoli, PA 19301-0947 • (610) 647-3575 • FAX (610) 647-2375

## **PRODUCT INFORMATION**

### **AMCO WETOIL**

(515)

#### **GENERAL CHARACTERISTICS AND USES**

*AMCO Wetoil* is an active, all-purpose, non-acid, non-fuming soldering flux. AMCO Wetoil addresses the need for a low temperature flux where soft alloys are used. It can be used on all ferrous and non-ferrous metals with the exception of aluminum and stainless steel. Applicable to both automated and manual processes. Contains neutralizing agents to minimize corrosion. Operating temperature range: 350 – 500 ° F. Conforms to Mil Spec AA51145C and OF 506C, Type II, Form B.

#### **PHYSICAL DATA**

- ◆ Water clear liquid.
- ◆ Specific Gravity: 1.56 @ 72 °F
- ◆ Weight per gallon: 13.0 lbs
- ◆ pH: 1.5 – 2.5

#### **PERFORMANCE CRITERIA**

- ◆ Residues are water soluble, slightly corrosive.
- ◆ Excellent wetting properties.
- ◆ Rapid surface reaction aids alloy dispersion.

#### **STORAGE & HANDLING**

- ◆ Shelf life. Indefinite in the unopened original container stored at room temperature.
- ◆ Use as received or can be diluted with water to desired reaction level.

#### **PACKAGING**

- ◆ Quart bottles – 12 per case
- ◆ Gallon jugs – 4 per case
- ◆ 5 gallon jugs
- ◆ 55 gallon drums

While we believe the data presented herein is accurate and reliable, the data are not to be taken as a guarantee or representation of any kind for which Force Industries assumes legal responsibility. They are offered solely for your consideration, investigation and verification.