

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Product Name: AMCO 105 CAS number: N/A - mixture
Chemical Name & Synonyms: N/A - mixture
Appearance: Fine, white powder with no characteristic odor.
Use: Aluminum furnace brazing flux.
Manufacturer: Force Industries Division Tel. 610-647-3575
EMERGENCY PHONE No. CALL CHEMTREC (800) 424-9300 * Available 24 Hours

II. CHEMICAL COMPOSITION

Material	SARA III	CAS Number	OSHA PEL	ACGIH TLV
Lithium Chloride	No	7447-41-8	5 mg/m ³	10 mg/m ³
Strontium Chloride	No	10476-85-4	-----	5.0 mg/m ³
Sodium fluoaluminate	No	7789-24-4	2.5 mg/m ³ as F	2.5 mg/m ³ as F
Potassium Fluoride	No	7789-23-3	2.5 mg/m ³ as F	2.5 mg/m ³ as F

Others, if any, are non-hazardous and are claimed as trade secret.

Note: Chronic fluoride absorption can result in ossious fluorosis, increased radiographic density of the bones and mottling of the teeth. Read OSHA 29 C.F.R. 1910.1000, July 1, 1980, (standard for fluoride).

Hazard Rating: HMIS: (H =2 F=0 R=0 PE=C) NFPA: (H=2 F=0 R=0)

III. POTENTIAL HEALTH EFFECTS AND HEALTH HAZARD DATA

Target organ statement: Caution: May be harmful if swallowed; irritating to skin and eyes.
Effects of Chronic Exposure: Coughing, CNS effects, erythema, nausea, and kidney effects.
Effects of Acute Overexposure
Swallowing: Nausea, vomiting. Can cause chemical burn to digestive system and toxic effects due to Lithium ion.
Skin Absorption: Not absorbed by skin.
Inhalation: Irritant to respiratory system. Lithium dust and fumes are absorbed through the lungs - lung damage. Pre-existing lung disorders will be aggravated.
Skin contact: May cause dermatitis; possible chemical burns. Existing skin disorders may be aggravated
Eye Contact: Irritation. Possible burn to eye surfaces.

IV. EMERGENCY AND FIRST AID PROCEDURES

Swallowing: Lithium and fluoride present. Call a physician or your Poison Control Center.
Skin: Wash hands with soap and water to remove all residue. If rash develops, consult a physician.
Inhalation: Remove to fresh air. If fumes, vapors, or dusts are inhaled, call a physician.
Eyes: Flush with water for at least 15 minutes to remove all residue. Promptly get medical help.

V. FIRE AND EXPLOSION DATA

Flashpoint (° F): N/A
Flammable limits in air: LOWER: N/A UPPER: N/A (% by volume)
Extinguishing media: Does not support combustion. Be aware of other materials in surrounding area to determine if water, fog, foam or CO₂ may be used
Special firefighting procedures: Metal halide and toxic fumes may be produced; use self contained breathing apparatus.
Unusual fire and explosion hazards: None.

VI. REACTIVITY INFORMATION

Stability considerations/Conditions to avoid: Stable/ None
Hazardous polymerization/Conditions to avoid: Will not occur/None
incompatibility/Materials to avoid: Strong acids, cyanides, and sulfides
Hazardous combustion or decomposition products: In presence of water and heat, HCl and HF may be given off.

MATERIAL SAFETY DATA SHEET

VII. SPILL AND LEAK RESPONSE

Steps to be taken if material is released or spilled: Contain spill, absorb, sweep-up. Remove to chemical sewer. Flush area to chemical sewer.

Waste disposal method: Dispose of in accordance with all local, state, and federal regulations.

VIII. SPECIAL PROTECTION INFORMATION

Respiratory protection: If the work station is not properly ventilated to exhaust all fumes, dusts, and vapors, use a NIOSH approved mask.

Ventilation: Maintain air flow away from user to remove all fumes, vapors, and dusts, so that the PEL is never exceeded.

Protective gloves: Chemical and oil impervious

Eye protection: Chemical tight safety goggles. Do not wear contact lenses.

Other protective equipment: Full protective equipment normally used in a braze/welding operation so as to prevent any contact. Review operations to avoid contact with hazardous gas, liquids or solids. See also:
29 CFR 1910.132 - 29 CFR 1910.140. Personal Protective Equipment
29 CFR 1910.251 - 29 CFR 1910.257. Welding, Cutting and Brazing

IX. STORAGE, HANDLING AND SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Wash hands thoroughly after handling to remove all residue. Store material under ambient conditions

Other precautions: Remove and professionally wash contaminated clothing before re-use.

X. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (°F @ 760 mmHg):	N/A	Bulk density, loose (lbs/cu.ft.)	46.8
Percent volatiles by volume:	N/A	Solubility in water:	Moderate
Evaporation rate (butyl acetate = 1):	N/A		

XI. OPTIONAL INFORMATION

Department of Transportation: DOMESTIC GROUND
Proper shipping name: Potassium Fluoride Mixture
Hazard Class: 6.1
ID & Packing Group Number: UN1812, PG III
ERG Guide Number: #154

Toxic Substance Control Act: All components of this compound are listed within the TSCA inventory.

Hazard Communication Program: Hazardous warnings and training requirements as mandated for Irritant material.

State Right-to-Know Programs:

Pennsylvania: This product contains the following chemicals listed in PA Code Title 34, Hazardous Substance List: None

California: This product contains the following compounds subject to the reporting and labeling requirements of Proposition 65:None

Miscellaneous: This product contains the following marine pollutants listed under 49 CFR 172.101 Appendix B: None

NOTES: NA=Not Applicable
H=Health

NE=Not Established
F=Fire

PE=Personal Equipment
R=Reactivity

While we believe all information presented herein is accurate and reliable, the data are not to be taken as a guarantee or representation of any kind for which Force Industries assumes legal responsibility. They are offered solely for your consideration, investigation, and verification.