

**FORCE  
INDUSTRIES  
DIVISION**

American Solder & Flux Co., Inc. • 28 Industrial Boulevard • Paoli, PA 19301-0947 • (610) 647-3575 • FAX (610) 647-2375

---

## **PRODUCT INFORMATION**

### **AMCO 4800 SOLDERING FLUX**

(608)

#### **GENERAL CHARACTERISTICS AND USES.**

**Amco 4800** is a water-based formulation designed to improve lug bond or weave in the const-on-strap battery construction process. Porosity is minimized through rapid evaporation enhancing bond integrity. Proven performance for over four decades, excellent results on all types of process equipment. Considered a charter formulation for the COS process.

#### **PHYSICAL DATA**

- ◆ Water clear with no characteristic odor.
- ◆ Specific Gravity: 1.04 – 1.06 @ 72 °F
- ◆ Weight per gallon: 8.66 – 8.83 lbs/gal
- ◆ Flash Pont: None
- ◆ Shelf Life: At least one year in the unopened original container stored at room temperature

#### **PERFORMANCE CRITERIA**

- ◆ Minimal residue, no adverse effect pm battery performance
- ◆ Use as received per casting equipment recommendation
- ◆ Excellent wetting and dispersion properties
- ◆ High yield per gallon

#### **STORAGE AND HANDLING**

- ◆ Shelf Life: At least 1 year in unopened container stored at room temperature
- ◆ Freezing does not affect performance, mix and reuse.

#### **PACKAGING**

- ◆ 1 gallon jug (4/carton)
- ◆ 5 gallon plastic jug.
- ◆ 55 gallon non returnable drum